

PRODUKTDATENBLATT

Magnetic filter grids of hard ferrite or NdFeB

Magnetic filter grids made of NdFeB, square, stainless steel housing 1.4301, screwed version









Article number	Lmm	B mm	H mm	Temperature °C	Number of magnetic filter bars	Diameter magnetic filter bars
MS100NdQu00rh00	100	100	40	80	2	25
MS150NdQu00rh00	150	150	40	80	3	25
MS200NdQu00rh00	200	200	40	80	4	25
MS250NdQu00rh00	250	250	40	80	5	25
MS300NdQu00rh00	300	300	40	80	6	25
MS350NdQu00rh00	350	350	40	80	7	25
MS400NdQu00rh01	400	400	40	80	8	25

APPLICATION:

Filter systems easily separate iron particles and chips being produced by abrasion or soiling from the material. Filters work reliably and almost wear-free. This extends the useful life of the production line and prevents the risk of expensive maintenance and cleaning work. The filtersystems are screwed and therefore easy to disassemble and to clean.

PRODUCT INFORMATION:

The above mentioned filter bars are our standard designs. Here the end pieces are not sealed tight and therefore only suitable for dry applications. The filter systems are screwed and therefore dismountable. This allows an easy and thorough cleaning of the filter as well as the exchange of components.

Not available ex stock, manufactured on demand

Alternative to the standard we also offer individual solutions:

- » Seal-welded model for use in liquids (e.g. water, coolant)
- » High-quality stainless steel enclosure for use in food production
- » Increasing the max. operating temperature up to 350 °C
- » Manufacture of individual, not standardised sizes