


Rubber coated systems

NdFeB magnetic system, black rubber sheath, with cylinder bore



Article number	D mm	d mm	d1 mm	H mm	h mm	Adhesive force* N	Shear force* N	Weight g	Temperature °C	Surface
A18C-KsB3.0H6	18	3	8.2	6	3,5	25	8	5.5	60	black
A22C-KsB4.0H6	22	4	8.2	6	3,5	38	15	8	60	black
A31C-KsB6.0H6	31	6	9	6	3,5	89	25	20	60	black
A31C-KsB6.0H8	31	6	9	8,5	3,5	89	25	20	60	black
A57C-KsB8.0H7.6	57	8	25	7,6	3,3	200	78	77	60	black
A66C-KsB5.5H8.5	66	5.5	22	8,5	3,2	250	85	100	80	black

PRODUCT NOTE:

These systems are particularly suitable for use on sensitive surfaces. The special rubber coating prevents scratches or discolouration on the surface. The displacement forces are also higher due to the rubber coating.

As an alternative to the standard system, we also offer customised solutions:

" Other colours for the rubber coating

" Harder or softer rubber coating

* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.